



Glo-Quartz® Incorporated
 1550 S. Euclid Ave., Tucson, AZ 85713
 520-792-2331 1-800-423-4078
 info@gloquartz.com

| DESCRIPTION OF HEATERS | KW | IMMERSION (IN) | PHASE | COMPATABLE | | |
|---|-----|----------------|---------------|---------------------|---------------------|----------|
| | | | | 240V | 480V | |
| | | | | 208/240V CONTROLLER | 440/480V CONTROLLER | |
| 1 1/2" 304 SS SCREWPLUG (2) .440" 304 SS ELEMENTS NEMA 1 TERMINAL HOUSING 20 W/SQ.IN. | 1 | 12 | 1 | PSSA-1DD12-E1 | PSSA-1II12-E1 | T2A |
| | 1.5 | 16 | 1 | PSSA-15DD16-E1 | PSSA-15II16-E1 | |
| | 2 | 20 | 1 | PSSA-2DD20-E1 | PSSA-2II20-E1 | |
| | 2.5 | 25 | 1 | PSSA-25DD25-E1 | PSSA-25II25-E1 | |
| | 3 | 30 | 1 | PSSA-3DD30-E1 | PSSA-3II30-E1 | |
| | 4 | 38 | 1 | PSSA-4DD38-E1 | PSSA-4II38-E1 | TC1-3430 |
| 5 | 47 | 1 | PSSA-5DD47-E1 | PSSA-5II47-E1 | | |
| 6 | 56 | 1 | PSSA-6DD56-E1 | PSSA-6II56-E1 | | |

THE CONTROLLERS HAVE AN ANALOG 60-250F STAT, FOR DIGITAL CHANGE TC1 TO TCD
 SEE "THERMOSTATS AND TERMINAL BOX OPTIONS" PAGE FOR OTHER HOUSING VARIATIONS

| ALTERNATE VOLTAGE CODES, REPLACE BLUE LETTERS IN THE P/N WITH CODES BELOW | |
|---|----------|
| A=120/1 | HH=415/3 |
| B=208/1 | I=440/1 |
| C=208/3 | J=440/3 |
| D=220/1 | Q=460/1 |
| E=220/3 | QQ=460/3 |
| BB=230/1 | II=480/1 |
| CC=230/3 | JJ=480/3 |
| DD=240/1 | K=550/1 |
| EE=240/3 | L=550/3 |
| F=277/1 | KK=575/1 |
| G=380/1 | LL=575/3 |
| H=380/3 | M=600/1 |
| GG=415/1 | N=600/3 |

| DESCRIPTION OF HEATERS | KW | IMMERSION (IN) | PHASE | COMPATABLE | | |
|---|-----|----------------|---------------|---------------------|---------------------|----------|
| | | | | 240V | 480V | |
| | | | | 208/240V CONTROLLER | 440/480V CONTROLLER | |
| 1 1/2" 304 SS SCREWPLUG (2) .440" 316 SS ELEMENTS NEMA 1 TERMINAL HOUSING 20 W/SQ.IN. | 1 | 12 | 1 | PSSB-1DD12-E1 | PSSB-1II12-E1 | T2A |
| | 1.5 | 16 | 1 | PSSB-15DD16-E1 | PSSB-15II16-E1 | |
| | 2 | 20 | 1 | PSSB-2DD20-E1 | PSSB-2II20-E1 | |
| | 2.5 | 25 | 1 | PSSB-25DD25-E1 | PSSB-25II25-E1 | |
| | 3 | 30 | 1 | PSSB-3DD30-E1 | PSSB-3II30-E1 | |
| | 4 | 38 | 1 | PSSB-4DD38-E1 | PSSB-4II38-E1 | TC1-3430 |
| 5 | 47 | 1 | PSSB-5DD47-E1 | PSSB-5II47-E1 | | |
| 6 | 56 | 1 | PSSB-6DD56-E1 | PSSB-6II56-E1 | | |



Glo-Quartz® Incorporated
 1550 S. Euclid Ave., Tucson, AZ 85713
 520-792-2331 1-800-423-4078
info@gloquartz.com

| DESCRIPTION OF HEATERS | KW | IMMERSION (IN) | PHASE | COMPATABLE | | |
|--|-----|----------------|-------|---------------------|---------------------|----------|
| | | | | 240V | 480V | |
| | | | | 208/240V CONTROLLER | 440/480V CONTROLLER | |
| 1 1/2" 304 SS SCREWPLUG (2) .440" ALLOY 800 ELEMENTS NEMA 1 TERMINAL HOUSING 20 W/SQ.IN. | 1 | 12 | 1 | PSN-1DD12-E1 | PSN-1II12-E1 | T2A |
| | 1.5 | 16 | 1 | PSN-15DD16-E1 | PSN-15II16-E1 | |
| | 2 | 20 | 1 | PSN-2DD20-E1 | PSN-2II20-E1 | |
| | 2.5 | 25 | 1 | PSN-25DD25-E1 | PSN-25II25-E1 | |
| | 3 | 30 | 1 | PSN-3DD30-E1 | PSN-3II30-E1 | |
| | 4 | 38 | 1 | PSN-4DD38-E1 | PSN-4II38-E1 | |
| | 5 | 47 | 1 | PSN-5DD47-E1 | PSN-5II47-E1 | TC1-3430 |
| | 6 | 56 | 1 | PSN-6DD56-E1 | PSN-6II56-E1 | |

THE CONTROLLERS HAVE AN ANALOG 60-250F STAT, FOR DIGITAL CHANGE TC1 TO TCD
 SEE "THERMOSTATS AND TERMINAL BOX OPTIONS" PAGE FOR OTHER HOUSING VARIATIONS

| ALTERNATE VOLTAGE CODES, REPLACE BLUE LETTERS IN THE P/N WITH CODES BELOW | |
|---|----------|
| A=120/1 | HH=415/3 |
| B=208/1 | I=440/1 |
| C=208/3 | J=440/3 |
| D=220/1 | Q=460/1 |
| E=220/3 | QQ=460/3 |
| BB=230/1 | II=480/1 |
| CC=230/3 | JJ=480/3 |
| DD=240/1 | K=550/1 |
| EE=240/3 | L=550/3 |
| F=277/1 | KK=575/1 |
| G=380/1 | LL=575/3 |
| H=380/3 | M=600/1 |
| GG=415/1 | N=600/3 |