



**Glo-Quartz® Incorporated**  
 1550 S. Euclid Ave., Tucson, AZ 85713  
 520-792-2331 1-800-423-4078  
 info@gloquartz.com

| DESCRIPTION OF HEATERS   | KW  | IMMERSION (IN) | PHASE | COMPATABLE          |                     |
|--|-----|----------------|-------|---------------------|---------------------|
|  |     |                |       | 110/120V CONTROLLER | 208/240V CONTROLLER |
| 1" 304 SS SCREWPLUG (1) .315" Dia 304 SS ELEMENT NEMA 1 TERMINAL HOUSING 40 W/SQ.IN. | 0.5 | 9              | 1     | SSA-5A9-E1          | SSA-5DD9-E1         |
|  | 1   | 15             | 1     | SSA-1A15-E1         | SSA-1DD15-E1        |
|  | 1.5 | 21             | 1     | SSA-15A21-E1        | SSA-15DD21-E1       |
|  | 2   | 28             | 1     | SSA-2A28-E1         | SSA-2DD28-E1        |
|  |     |                |       | T2A                 | T2A                 |

| ALTERNATE VOLTAGE CODES, REPLACE BLUE LETTERS IN THE P/N WITH CODES BELOW |          |
|---|----------|
| A=120/1   | HH=415/3 |
| B=208/1   | I=440/1  |
| C=208/3   | J=440/3  |
| D=220/1   | Q=460/1  |
| E=220/3   | QQ=460/3 |
| BB=230/1  | II=480/1 |
| CC=230/3  | JJ=480/3 |
| DD=240/1  | K=550/1  |
| EE=240/3  | L=550/3  |
| F=277/1   | KK=575/1 |
| G=380/1   | LL=575/3 |
| H=380/3   | M=600/1  |
| GG=415/1  | N=600/3  |

THE CONTROLLERS HAVE AN ANALOG 60-250F STAT, FOR DIGITAL CHANGE TC1 TO TCD  
 SEE "THERMOSTATS AND TERMINAL BOX OPTIONS" PAGE FOR OTHER HOUSING VARIATIONS

| DESCRIPTION OF HEATERS   | KW  | IMMERSION (IN) | PHASE | COMPATABLE          |                     |
|--|-----|----------------|-------|---------------------|---------------------|
|  |     |                |       | 110/120V CONTROLLER | 208/240V CONTROLLER |
| 1" 304 SS SCREWPLUG (1) .315" Dia 316 SS ELEMENT NEMA 1 TERMINAL HOUSING 40 W/SQ.IN. | 0.5 | 9              | 1     | SSB-5A9-E1          | SSB-5DD9-E1         |
|  | 1   | 15             | 1     | SSB-1A15-E1         | SSB-1DD15-E1        |
|  | 1.5 | 21             | 1     | SSB-15A21-E1        | SSB-15DD21-E1       |
|  | 2   | 28             | 1     | SSB-2A28-E1         | SSB-2DD28-E1        |
|  |     |                |       | T2A                 | T2A                 |



**Glo-Quartz® Incorporated**

1550 S. Euclid Ave., Tucson, AZ 85713  
 520-792-2331 1-800-423-4078  
[info@gloquartz.com](mailto:info@gloquartz.com)

| DESCRIPTION OF HEATERS  | KW  | IMMERSION (IN) | PHASE | COMPATABLE          |                     |
|---|-----|----------------|-------|---------------------|---------------------|
|   |     |                |       | 110/120V CONTROLLER | 208/240V CONTROLLER |
| 1" 304 SS SCREWPLUG (1) .315" Dia ALLOY 800 ELEMENT NEMA 1 TERMINAL HOUSING 40 W/SQ.IN. | 0.5 | 9              | 1     | 120V                | 240V                |
|   | 1   | 15             | 1     | SN-5A9-E1           | SN-5DD9-E1          |
|   | 1.5 | 21             | 1     | SN-1A15-E1          | SN-1DD15-E1         |
|   | 2   | 28             | 1     | SN-15A21-E1         | SN-15DD21-E1        |
|   |     |                |       | SN-2A28-E1          | SN-2DD28-E1         |
|   |     |                |       | T2A                 | T2A                 |

THE CONTROLLERS HAVE AN ANALOG 60-250F STAT, FOR DIGITAL CHANGE TC1 TO TCD  
 SEE "THERMOSTATS AND TERMINAL BOX OPTIONS" PAGE FOR OTHER HOUSING VARIATIONS

| ALTERNATE VOLTAGE CODES,<br>REPLACE BLUE LETTERS IN<br>THE P/N WITH CODES BELOW |          |
|---|----------|
| A=120/1   | HH=415/3 |
| B=208/1   | I=440/1  |
| C=208/3   | J=440/3  |
| D=220/1   | Q=460/1  |
| E=220/3   | QQ=460/3 |
| BB=230/1  | II=480/1 |
| CC=230/3  | JJ=480/3 |
| DD=240/1  | K=550/1  |
| EE=240/3  | L=550/3  |
| F=277/1   | KK=575/1 |
| G=380/1   | LL=575/3 |
| H=380/3   | M=600/1  |
| GG=415/1  | N=600/3  |