



Glo-Quartz® Incorporated
 1550 S. Euclid Ave., Tucson, AZ 85713
 520-792-2331 1-800-423-4078
info@gloquartz.com

DESCRIPTION OF HEATERS	KW	IMMERSION (IN)	COMPATABLE 110/120V CONTROLLER		COMPATABLE 208/240V CONTROLLER		COMPATABLE 440/480V CONTROLLER	
			120/1	240/1	480/1	440/480V		
OVER THE SIDE SINGLE ELEMENT 304 SS 40 W/SQ.IN.	1	18	WSA-1A18	T2A	WSA-1DD18	T2A		TC1-3430
	1.5	22	WSA-15A22		WSA-15DD22			
	2	28	WSA-2A28		WSA-2DD28		WSA-2II28	
	2.5	30		TC1-330	WSA-25DD30	WSA-25II30		
	3	34			WSA-3DD34	WSA-3II34		
	3.5	40			WSA-35DD40	WSA-35II40		
	4	45			WSA-4DD45	WSA-4II45		
	4.5	50			WSA-45DD50	WSA-45II50		
	5	55			WSA-5DD55	WSA-5II55		
6	65		WSA-6DD65		WSA-6II65			
7	70		WSA-7DD70	WSA-7II70				

ALTERNATE VOLTAGE CODES, REPLACE BLUE LETTERS IN THE P/N WITH CODES BELOW	
A=120/1	HH=415/3
B=208/1	I=440/1
C=208/3	J=440/3
D=220/1	Q=460/1
E=220/3	QQ=460/3
BB=230/1	II=480/1
CC=230/3	JJ=480/3
DD=240/1	K=550/1
EE=240/3	L=550/3
F=277/1	KK=575/1
G=380/1	LL=575/3
H=380/3	M=600/1
GG=415/1	N=600/3

THE CONTROLLERS HAVE AN ANALOG 60-250F STAT, FOR DIGITAL CHANGE TC1 TO TCD

DESCRIPTION OF HEATERS	KW	IMMERSION (IN)	COMPATABLE 110/120V CONTROLLER		COMPATABLE 208/240V CONTROLLER		COMPATABLE 440/480V CONTROLLER	
			120/1	240/1	480/1	440/480V		
OVER THE SIDE SINGLE ELEMENT 316 SS 40 W/SQ.IN.	1	18	WSB-1A18	T2A	WSB-1DD18	T2A		TC1-3430
	1.5	22	WSB-15A22		WSB-15DD22			
	2	28	WSB-2A28		WSB-2DD28		WSB-2II28	
	2.5	30		TC1-330	WSB-25DD30	WSB-25II30		
	3	34			WSB-3DD34	WSB-3II34		
	3.5	40			WSB-35DD40	WSB-35II40		
	4	45			WSB-4DD45	WSB-4II45		
	4.5	50			WSB-45DD50	WSB-45II50		
	5	55			WSB-5DD55	WSB-5II55		
6	65		WSB-6DD65		WSB-6II65			
7	70		WSB-7DD70	WSB-7II70				



Glo-Quartz® Incorporated
 1550 S. Euclid Ave., Tucson, AZ 85713
 520-792-2331 1-800-423-4078
info@gloquartz.com

DESCRIPTION OF HEATERS	KW	IMMERSION (IN)	COMPATABLE 110/120V CONTROLLER		COMPATABLE 208/240V CONTROLLER		COMPATABLE 440/480V CONTROLLER	
			120/1	240/1	480/1	440/480V		
OVER THE SIDE SINGLE ELEMENT ALLOY 800 40 W/SQ.IN.	1	18	WN-1A18	T2A	WN-1DD18	T2A		TC1-3430
	1.5	22	WN-15A22		WN-15DD22			
	2	28	WN-2A28		WN-2DD28		WN-2II28	
	2.5	30		WN-25DD30	TC1-330	WN-25II30		
	3	34		WN-3DD34		WN-3II34		
	3.5	40		WN-35DD40		WN-35II40		
	4	45		WN-4DD45		WN-4II45		
	4.5	50		WN-45DD50		WN-45II50		
	5	55		WN-5DD55		WN-5II55		
6	65		WN-6DD65	WN-6II65				
7	70		WN-7DD70	WN-7II70				

ALTERNATE VOLTAGE CODES, REPLACE BLUE LETTERS IN THE P/N WITH CODES BELOW	
A=120/1	HH=415/3
B=208/1	I=440/1
C=208/3	J=440/3
D=220/1	Q=460/1
E=220/3	QQ=460/3
BB=230/1	II=480/1
CC=230/3	JJ=480/3
DD=240/1	K=550/1
EE=240/3	L=550/3
F=277/1	KK=575/1
G=380/1	LL=575/3
H=380/3	M=600/1
GG=415/1	N=600/3

THE CONTROLLERS HAVE AN ANALOG 60-250F STAT, FOR DIGITAL CHANGE TC1 TO TCD

DESCRIPTION OF HEATERS	KW	IMMERSION (IN)	COMPATABLE 110/120V CONTROLLER		COMPATABLE 208/240V CONTROLLER		COMPATABLE 440/480V CONTROLLER	
			120/1	240/1	480/1	440/480V		
OVER THE SIDE SINGLE ELEMENT TITANIUM 40 W/SQ.IN.	1	18	WT-1A18	T2A	WT-1DD18	T2A		TC1-3430
	1.5	22	WT-15A22		WT-15DD22			
	2	28	WT-2A28		WT-2DD28		WT-2II28	
	2.5	30		WT-25DD30	TC1-330	WT-25II30		
	3	34		WT-3DD34		WT-3II34		
	3.5	40		WT-35DD40		WT-35II40		
	4	45		WT-4DD45		WT-4II45		
	4.5	50		WT-45DD50		WT-45II50		
	5	55		WT-5DD55		WT-5II55		
6	65		WT-6DD65	WT-6II65				
7	70		WT-7DD70	WT-7II70				