



Glo-Quartz® Incorporated
 1550 S. Euclid Ave., Tucson, AZ 85713
 520-792-2331 1-800-423-4078
 info@gloquartz.com

DESCRIPTION OF HEATERS	KW	IMMERSION (IN)	PHASE	COMPATABLE		
				240V	480V	
				208/240V CONTROLLER	440/480V CONTROLLER	
1 1/2" 304 SS SCREWPLUG (2) .440" 304 SS ELEMENTS NEMA 1 TERMINAL HOUSING 40 W/SQ.IN.	1.5	9	1	PSSA-15DD9-E1	PSSA-15II9-E1	T2A
	2	11	1	PSSA-2DD11-E1	PSSA-2II11-E1	
	2.5	13	1	PSSA-25DD13-E1	PSSA-25II13-E1	
	3	16	1	PSSA-3DD16-E1	PSSA-3II16-E1	TC1-3430
	4	20	1	PSSA-4DD20-E1	PSSA-4II20-E1	
	5	25	1	PSSA-5DD25-E1	PSSA-5II25-E1	
	6	29	1	PSSA-6DD29-E1	PSSA-6II29-E1	
	7	34	1	PSSA-7DD34-E1	PSSA-7II34-E1	
	9	43	1	PSSA-9DD43-E1	PSSA-9II43-E1	
				TC1-350		

ALTERNATE VOLTAGE CODES, REPLACE BLUE LETTERS IN THE P/N WITH CODES BELOW	
A=120/1	HH=415/3
B=208/1	I=440/1
C=208/3	J=440/3
D=220/1	Q=460/1
E=220/3	QQ=460/3
BB=230/1	II=480/1
CC=230/3	JJ=480/3
DD=240/1	K=550/1
EE=240/3	L=550/3
F=277/1	KK=575/1
G=380/1	LL=575/3
H=380/3	M=600/1
GG=415/1	N=600/3

THE CONTROLLERS HAVE AN ANALOG 60-250F STAT, FOR DIGITAL CHANGE TC1 TO TCD
 SEE "THERMOSTATS AND TERMINAL BOX OPTIONS" PAGE FOR OTHER HOUSING VARIATIONS

DESCRIPTION OF HEATERS	KW	IMMERSION (IN)	PHASE	COMPATABLE		
				240V	480V	
				208/240V CONTROLLER	440/480V CONTROLLER	
1 1/2" 304 SS SCREWPLUG (2) .440" 316 SS ELEMENTS NEMA 1 TERMINAL HOUSING 40 W/SQ.IN.	1.5	9	1	PSSB-15DD9-E1	PSSB-15II9-E1	T2A
	2	11	1	PSSB-2DD11-E1	PSSB-2II11-E1	
	2.5	13	1	PSSB-25DD13-E1	PSSB-25II13-E1	
	3	16	1	PSSB-3DD16-E1	PSSB-3II16-E1	TC1-3430
	4	20	1	PSSB-4DD20-E1	PSSB-4II20-E1	
	5	25	1	PSSB-5DD25-E1	PSSB-5II25-E1	
	6	29	1	PSSB-6DD29-E1	PSSB-6II29-E1	
	7	34	1	PSSB-7DD34-E1	PSSB-7II34-E1	
	9	43	1	PSSB-9DD43-E1	PSSB-9II43-E1	
				TC1-350		



Glo-Quartz® Incorporated
 1550 S. Euclid Ave., Tucson, AZ 85713
 520-792-2331 1-800-423-4078
info@gloquartz.com

DESCRIPTION OF HEATERS	KW	IMMERSION (IN)	PHASE	240V		COMPATABLE	480V	COMPATABLE
						208/240V CONTROLLER		440/480V CONTROLLER
1 1/2" 304 SS SCREWPLUG (2) .440" ALLOY 800 ELEMENTS NEMA 1 TERMINAL HOUSING 40 W/SQ.IN.	1.5	9	1	PSN-15DD9-E1	T2A	T2A	PSN-15II9-E1	T2A
	2	11	1	PSN-2DD11-E1			PSN-2II11-E1	
	2.5	13	1	PSN-25DD13-E1			PSN-25II13-E1	
	3	16	1	PSN-3DD16-E1			PSN-3II16-E1	
	4	20	1	PSN-4DD20-E1			PSN-4II20-E1	
	5	25	1	PSN-5DD25-E1			PSN-5II25-E1	
	6	29	1	PSN-6DD29-E1			PSN-6II29-E1	
	7	34	1	PSN-7DD34-E1			PSN-7II34-E1	
	9	43	1	PSN-9DD43-E1	TC1-350	PSN-9II43-E1	TC1-3430	

THE CONTROLLERS HAVE AN ANALOG 60-250F STAT, FOR DIGITAL CHANGE TC1 TO TCD
 SEE "THERMOSTATS AND TERMINAL BOX OPTIONS" PAGE FOR OTHER HOUSING VARIATIONS

ALTERNATE VOLTAGE CODES, REPLACE BLUE LETTERS IN THE P/N WITH CODES BELOW	
A=120/1	HH=415/3
B=208/1	I=440/1
C=208/3	J=440/3
D=220/1	Q=460/1
E=220/3	QQ=460/3
BB=230/1	II=480/1
CC=230/3	JJ=480/3
DD=240/1	K=550/1
EE=240/3	L=550/3
F=277/1	KK=575/1
G=380/1	LL=575/3
H=380/3	M=600/1
GG=415/1	N=600/3