



Glo-Quartz® Incorporated
 1550 S. Euclid Ave., Tucson, AZ 85713
 520-792-2331 1-800-423-4078
 info@gloquartz.com

DESCRIPTION OF HEATERS	KW	HEATER LENGTH (IN)	RISER HEIGHT (IN)	COMPATABLE 110/120V CONTROLLER		COMPATABLE 208/240V CONTROLLER		COMPATABLE 440/480V CONTROLLER	
				120/1	240/1	208/240V	480/1	440/480V	
"L" STYLE BOTTOM TANK HEATER 1 ELEMENT 304 SS 20 W/SQ.IN.	0.5	14	36"	LSA-5A14-R36	T2A	LSA-5DD14-R36	TC1-330		TC1-3430
	1	24	36"	LSA-1A24-R36		LSA-1DD24-R36			
	1.5	32	36"	LSA-15A32-R36		LSA-15DD32-R36			
	2	42	36"	LSA-2A42-R36	LSA-2DD42-R36				
	2.5	52	48"		LSA-25DD52-R48			LSA-25II52-R48	
	3	57	48"		LSA-3DD57-R48			LSA-3II57-R48	
3.5	67	48"		LSA-35DD67-R48		LSA-35II67-R48			

ALTERNATE VOLTAGE CODES, REPLACE BLUE LETTERS IN THE P/N WITH CODES BELOW	
A=120/1	HH=415/3
B=208/1	I=440/1
C=208/3	J=440/3
D=220/1	Q=460/1
E=220/3	QQ=460/3
BB=230/1	II=480/1
CC=230/3	JJ=480/3
DD=240/1	K=550/1
EE=240/3	L=550/3
F=277/1	KK=575/1
G=380/1	LL=575/3
H=380/3	M=600/1
GG=415/1	N=600/3

THE CONTROLLERS HAVE AN ANALOG 60-250F STAT, FOR DIGITAL CHANGE TC1 TO TCD

DESCRIPTION OF HEATERS	KW	HEATER LENGTH (IN)	RISER HEIGHT (IN)	COMPATABLE 110/120V CONTROLLER		COMPATABLE 208/240V CONTROLLER		COMPATABLE 440/480V CONTROLLER	
				120/1	240/1	208/240V	480/1	440/480V	
"L" STYLE BOTTOM TANK HEATER 1 ELEMENT 316 SS 20 W/SQ.IN.	0.5	14	36"	LSB-5A14-R36	T2A	LSB-5DD14-R36	TC1-330		TC1-3430
	1	24	36"	LSB-1A24-R36		LSB-1DD24-R36			
	1.5	32	36"	LSB-15A32-R36		LSB-15DD32-R36			
	2	42	36"	LSB-2A42-R36	LSB-2DD42-R36				
	2.5	52	48"		LSB-25DD52-R48			LSB-25II52-R48	
	3	57	48"		LSB-3DD57-R48			LSB-3II57-R48	
3.5	67	48"		LSB-35DD67-R48		LSB-35II67-R48			



Glo-Quartz® Incorporated

1550 S. Euclid Ave., Tucson, AZ 85713
 520-792-2331 1-800-423-4078
 info@gloquartz.com

DESCRIPTION OF HEATERS	KW	HEATER LENGTH (IN)	RISER HEIGHT (IN)	COMPATABLE		COMPATABLE		COMPATABLE	
				120/1	110/120V CONTROLLER	240/1	208/240V CONTROLLER	480/1	440/480V CONTROLLER
"L" STYLE BOTTOM TANK HEATER 1 ELEMENT ALLOY 800 20 W/SQ.IN.	0.5	14	36"	LN-5A14-R36	T2A	LN-5DD14-R36	TC1-330	LN-2II42-R36	TC1-3430
	1	24	36"	LN-1A24-R36		LN-1DD24-R36			
	1.5	32	36"	LN-15A32-R36		LN-15DD32-R36			
	2	42	36"	LN-2A42-R36	LN-2DD42-R36				
	2.5	52	48"		LN-25DD52-R48				
	3	57	48"		LN-3DD57-R48				
3.5	67	48"		LN-35DD67-R48		LN-35II67-R48			

THE CONTROLLERS HAVE AN ANALOG 60-250F STAT, FOR DIGITAL CHANGE TC1 TO TCD

ALTERNATE VOLTAGE CODES, REPLACE BLUE LETTERS IN THE P/N WITH CODES BELOW	
A=120/1	HH=415/3
B=208/1	I=440/1
C=208/3	J=440/3
D=220/1	Q=460/1
E=220/3	QQ=460/3
BB=230/1	II=480/1
CC=230/3	JJ=480/3
DD=240/1	K=550/1
EE=240/3	L=550/3
F=277/1	KK=575/1
G=380/1	LL=575/3
H=380/3	M=600/1
GG=415/1	N=600/3