



Glo-Quartz® Incorporated
 1550 S. Euclid Ave., Tucson, AZ 85713
 520-792-2331 1-800-423-4078
info@gloquartz.com

DISCRIPTION	CAT#	TEMP RANGE (F)	AMPS	SENSOR LENGTH
SINGLE POLE SINGLE THROW (SPST) 120/240 VOLTS THERMOSTATS	T1A	30-120	16	67" COPPER CAPILARY
	T1A-WB	30-120	16	67" COPPER CAPILARY
	T1B	60-250	16	64" COPPER CAPILARY
	T1B-WB	60-250	16	64" COPPER CAPILARY
	T1C	175-550	20	6' STEEL CAPILARY
	T1C-WB	175-550	20	6' STEEL CAPILARY
	T1JA	0-100	20	10' J THERMOCOUPLE
	T1JA-WB	0-100	20	10' J THERMOCOUPLE
	T1JB	60-250	20	10' J THERMOCOUPLE
	T1JB-WB	60-250	20	10' J THERMOCOUPLE
	T1JC	175-550	20	10' J T'C & 15" PROBE
	T1JC-WB	175-550	20	10' J T'C & 15" PROBE
	T1RB	60-250	20	4' RTD SENSOR
	T1RB-WB	60-250	20	4' RTD SENSOR
T1RB-LCD	60-250	20	4' RTD SENSOR	

WB = WITHOUT BOX

DISCRIPTION	CAT#	TEMP RANGE (F)	AMPS	SENSOR LENGTH
DOUBLE POLE SINGLE THROW (DPST) 120/240 VOLTS (10 AMPS ON 480 VOLTS) THERMOSTATS	T2A	60-250	30	64" COPPER CAPILARY
	T2A-WB	60-250	30	64" COPPER CAPILARY
	T2AL	0-100	30	64" COPPER CAPILARY
	T2AL-WB	0-100	30	64" COPPER CAPILARY